

Cod. 10131

Spring

Solid set systems
Cobertura integral



Full-circle impact sprinkler with rear nozzle driven arm

Aspersor circular de impacto, con brazo oscilante accionado por la boquilla posterior



Net weight
Peso neto
0,76 kg

Connection
Conexión
1" F

Size
Dimensiones
ø 272 mm x 186 mm

Nozzle
Boquilla
ø 4 ÷ 10 mm

Angle
Ángulo
30°

Pressure *Presion*

for **US units** go to page 69

| Nozzle <i>Boquilla</i> | 1,5 bar | | 2 bar | | 3 bar | | 4 bar | |
|---------------------------|--------------------------------|-------------------------------|--------------------------------|-------------------------------|--------------------------------|-------------------------------|--------------------------------|-------------------------------|
| | Flow <i>Caudal</i> l/min | Radius <i>Alcance</i> m | Flow <i>Caudal</i> l/min | Radius <i>Alcance</i> m | Flow <i>Caudal</i> l/min | Radius <i>Alcance</i> m | Flow <i>Caudal</i> l/min | Radius <i>Alcance</i> m |
| 5 mm - 5 mm | 39 | 12,5 | 45 | 13,5 | 55 | 15,5 | 64 | 17 |
| 5 mm - 6 mm | 47 | 13 | 54 | 15 | 66 | 17 | 77 | 18 |
| 5 mm - 7 mm | 57 | 14,5 | 64 | 15,5 | 79 | 17,5 | 92 | 18,5 |
| 5 mm - 9 mm | 82 | 16 | 93 | 17 | 114 | 19 | 132 | 20,5 |